PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5 :
E21B 47/12, G08C 23/00

A1

(11) International Publication Number: WO 92/06278

(43) International Publication Date: 16 April 1992 (16.04.92)

(21) International Application Number: PCT/GB91/01599

(22) International Filing Date: 18 September 1991 (18.09.91)

(30) Priority data:
9021253.1 29 September 1990 (29.09.90) GB

(71) Applicant *(for all designated States except US)*: METROL TECHNOLOGY LIMITED [GB/GB]; 1 Whitemyres Avenue, Mastrick, Aberdeen AB2 6HQ (GB).

(72) Inventor; and
(75) Inventor/Applicant *(for US only)* : SMITH, David, Balfour [GB/GB]; East Neuk, Netherley, Stonehaven, Kincardinshire AB3 2NQ (GB).

(74) Agent: PATTULLO, Norman; Murgitroyd and Company, Mitchell House, 333 Bath Street, Glasgow G2 4ER (GB).

(81) Designated States: AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI patent), BR, CA, CF (OAPI patent), CG (OAPI patent), CH (European patent), CI (OAPI patent), CM (OAPI patent), CS, DE (European patent), DK (European patent), ES (European patent), FI, FR (European patent), GA (OAPI patent), GB, GB (European patent), GN (OAPI patent), GR (European patent), HU, IT (European patent), JP, KP, KR, LK, LU (European patent), MC, MG, ML (OAPI patent), MR (OAPI patent), MW, NL (European patent), NO, PL, RO, SD, SE (European patent), SN (OAPI patent), SU+,TD (OAPI patent), TG (OAPI patent), US.

Published
With international search report.

(54) Title: TRANSMISSION OF DATA IN BOREHOLES

(57) *Abstract*

Data is transmitted along a borehole containing a drill stem (2) by means of a transmitter (6) which converts electric data signals to acoustic signals propagating along the drill stem (2). The acoustic signals are converted back to electric form by a receiver (12) which also processes the signals. In the preferred form the signals are stored in a receiver memory (15) for subsequent retrieval using a pick-up tool (5) lowered into the borehole. The system is particularly useful in moving data past an obstruction such as a shut-in valve (4).



+ DESIGNATIONS OF "SU"

Any designation of "SU" has effect in the Russian Federation. It is not yet known whether any such designation has effect in other States of the former Soviet Union.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland			SN	Senegal
CI	Côte d'Ivoire	KR	Republic of Korea	SU+	Soviet Union
CM	Cameroon	LI	Liechtenstein	TD	Chad
CS	Czechoslovakia	LK	Sri Lanka	TG	Togo
DE	Germany	LU	Luxembourg	US	United States of America
DK	Denmark	MC	Monaco		

"Transmission of Data in Boreholes"

This invention relates to a method of and apparatus for transmitting data in boreholes such as oil wells.

To optimise the efficiency both of the detection of oil reserves and the recovery of these reserves, it is important to obtain as much detailed information as possible about the ambient environmental conditions at the base of an oil well. This information is obtained by a variety of sensors located at the base of a well when required. The information obtained by the sensors may be transmitted to the surface of an open well using sonic waves which propagate through the drilling mud.

However, this method may only be employed during drilling when sufficient hydraulic power is available to generate the signal at the base of the well. During well testing and production this power source is not available and a valve or plug may be inserted in the well resulting in there being no direct fluid path through the centre of the well from the base of the well to the surface.

One situation to which this particularly applies is in

shut-in testing where a shut-in valve is included in the well. A test generally consists of flowing the well, thus drawing down the well pressure, and then suddenly stopping the flow by closing the shut-in valve. Information regarding the potential of the reservoir can be derived from examination of the ensuing pressure rise/time characteristic, requiring a pressure gauge beneath the valve. The shut-in is best done down-hole rather than at the surface, to avoid well-bore storage effects which are difficult to compensate for.

It is possible to adapt valves to produce a hydraulic or electrical path through the valve to enable the transmission of signals from a sensor below the valve to a receiver above the valve. The path through the valve terminates in a connector which is suitable for connection to the receiver, the receiver in turn being connected via a cable to the surface of the well. However, this system is extremely difficult to operate as the small connector on the surface of the valve is extremely difficult to contact with the receiver and a considerable length of time is taken to make a suitable connection.

Accordingly, the present invention provides a method of transmitting data in a borehole, the method comprising providing an electric signal representative of the data to be transmitted, converting said electric signal into a sonic signal, propagating said sonic signal along an elongate member, and processing the sonic signal for onward transmission.

The processing of the sonic signal may for example be at the surface, or it may be downhole by retransmission

or it may be by electronic data storage for later pick-up.

In another aspect, the invention provides apparatus for transmitting data in a borehole, the apparatus comprising a transmitter and a receiver; the transmitter including means for converting data parameters into an electric signal and first transducer means responsive to said electric signal to generate an acoustic signal, the first transducer means being adapted for physical coupling to an elongate member extending along the borehole whereby the acoustic signal is propagated in said elongate member; the receiver comprising second transducer means adapted for physical coupling to said elongate member to produce an electrical output corresponding to said acoustic signal, and signal processing means connected to receive said output and operative to process the data into a condition for onward transmission.

An embodiment of the invention will now be described, by way of example only, with reference to the drawings, in which:

Fig. 1 is a schematic cross-sectional side view of apparatus in accordance with the invention in use in a well;
Fig. 2 is a block diagram of a transmitter forming part of Fig. 1;
Fig. 3 is a block diagram of a receiver forming part of Fig. 1; and
Fig. 4 is a block diagram of an alternative form of receiver.

Referring to Fig. 1, a drill stem 1 is sealed to a well

bore 23 by a packer 2, leaving an annulus 3 to contain mud and well control fluid. Any production fluids will pass up the centre of the drill stem 1 via a shut-in valve 4. The present embodiment utilises the invention to pass data relating to the fluid pressure in the drill stem bore 24 below the shut-in valve 4 to a location above it.

A transmitter designated generally at 6 is positioned in an external recess 25 of the drill stem 1. The transmitter 6 is powered by a battery 7 and includes a pressure transducer 9 communicating with a lower bore 24 via a port 8. The analog pressure signal generated by the transducer 9 passes to an electronics module 10 in which it is digitised and serially encoded for transmission by a carrier frequency, suitably of 2-10 kHz. The resulting bursts of carrier are applied to a magnetostrictive transducer 11 comprising a coil formed around a core whose ends are rigidly fixed to the drill stem 1 at axially spaced locations. The digitally coded data is thus transformed into a longitudinal sonic wave in the drill stem 1.

A receiver generally designated at 12 is housed in an external recess 26 of the drill stem 1 at a location above the shut-in valve 4. The receiver 12 comprises a filter 13 and transducer 14 connected to an electronics module 15 powered by a battery 17.

The output of the electronics module 15 drives a signal coil 16.

The filter 13 is a mechanical band-pass filter tuned to the data carrier frequency, and serves to remove some of the acoustic noise in the drill stem 1 which could

otherwise swamp the electronics. The transducer 14 is a piezoelectric element. The filter 13 and transducer 14 are mechanically coupled in series, and the combination is rigidly mounted at its ends to the drill stem 1, aligned with the longitudinal axis of the latter. Thus, the transducer 14 provides an electrical output representative of the sonic data signal.

A preferred method of retrieving the data is to store it in memory in the electronics module 15, for retrieval at a convenient time by a pick-up tool 5. This avoids the problems inherent in providing a real-time data path along the whole length of the well. The pick-up tool 5 is lowered on a cable or wireline 22 to locate in a nipple 18 which causes the signal in the receiver 16 to be aligned with a coil 19 in the pick-up tool 5. The coils 16 and 19 are then inductively coupled, allowing the data to be transferred to the pick-up tool 5 serially on a suitable carrier wave to the pick-up tool 5.

The pick-up tool 5 includes an electronics package 20 which is arranged to send a transmit command to the receiver 12 when the tool 5 is seated on the nipple 18. The electronics package 20 may be arranged to decode and store the data if the tool is on wireline, or to re-transmit the data if the tool is on cable. In the latter case, power may be supplied to the tool via the cable; otherwise, power is derived from an internal battery 21.

Referring now to Fig. 2, the transmitter electronics module 10 in the present embodiment comprises a signal conditioning circuit 30, a digitising and encoding circuit 31, and a current driver 32. The details of

these circuits do not form part of the present invention, and suitable circuitry will be readily apparent to those skilled in the art. The transducer 11 has a coil 33 connected to the current driver 32 and formed round a core schematically indicated at 34. Suitably, the core is a laminated rod of nickel of about 25 mm diameter. The length of the rod is chosen to suit the desired sonic frequency which is suitably in the range 100 Hz to 10kHz, preferably 2-6 kHz.

In the receiver, as seen in Fig. 3, the electronics module 15 comprises in series as passive band-pass filter 35, an active band-pass filter 36, and a phase-locked loop 37 supplying clean data signals to a decoder 38. The decoded data is stored in memory 39. When a pick-up tool 5 is positioned and activated, carrier frequency induced in the signal coil 16 is detected at 40 to enable control logic 41 to read data from memory 39 for transmission via encoder 42, current driver 43, and the signal coil 16.

The alternative receiver shown in Fig. 4 uses a similar mechanical filter 13, transducer 14, and electronic filters 35 and 36. In this case, however, the filtered data signal is not stored but is used to control a current driver 44 driving a magnetostrictive transducer 45 for sonic re-transmission further along the drill stem.

Thus, the invention enables data to be transferred by sonic transmission past a valve or the like and then further handled by (a) storage in memory for later retrieval, (b) real-time transmission electrically by cable, or (c) sonic re-transmission.

Modifications may be made within the scope of the invention. For example, the transmitter transducer may impart a torsional, rather than a longitudinal, sonic vibration to the drill stem. Transducers of other than magnetostrictive type may be used, such as piezoelectric crystals or polymers.

Although described with particular reference to shut-in testing in producing wells, the invention may be applied to any situation where a borehole is obstructed. The medium for sonic transmission need not be a drill stem but could, for instance, be casing or other tubular.

CLAIMS

1. A method of transmitting data in a borehole, the method comprising providing an electric signal representative of the data to be transmitted, converting said electric signal into a sonic signal, propagating said sonic signal along an elongate member, and processing the sonic signal for onward transmission.

2. A method according to claim 1, in which data is transmitted from one side to the other of a physical obstruction in said elongate member, the conversion of the electric signal into the sonic signal being effected at a location on said one side, and the processing being effected at said other side.

3. A method according to claim 1 or claim 2, in which said processing comprises storing the data for subsequent retrieval.

4. A method according to claim 3, in which the subsequent retrieval is effected by a pick-up tool lowered down the borehole to a location adjacent the obstruction.

5. A method according to claim 1 or claim 2, in which said processing comprises sonic re-transmission.

6. A method according to any one of the preceding claims, in which conversion from the electric signal to the sonic signal includes digital modulation of a carrier frequency in the range 100 Hz to 10 kHz.

7. A method according to any one of the preceding claims, in which the sonic transmission is effected by longitudinal vibration.

8. A method according to claim 2, in which the elongate member is a drill stem, the obstruction is a shut-in valve in the drill stem, and the data comprises pressure-versus-time in the drill stem beneath the shut-in valve.

9. Apparatus for transmitting data in a borehole, the apparatus comprising a transmitter and a receiver; the transmitter including means for converting data parameters into an electric signal and first transducer means responsive to said electric signal to generate an acoustic signal, the first transducer means being adapted for physical coupling to an elongate member extending along the borehole whereby the acoustic signal is propagated in said elongate member; the receiver comprising second transducer means adapted for physical coupling to said elongate member to produce an electrical output corresponding to said acoustic signal, and signal processing means connected to receive said output and operative to process the data into a condition for onward transmission.

10. Apparatus according to claim 9 for use in transmitting data from one side to the other of an obstruction in said elongate member, the first transducer means being coupled, in use, to the elongate member at a location on said one side of the obstruction, and the second transducer means being coupled, in use, to the elongate member at the other side of the obstruction.

11. Apparatus according to claim 9 or claim 10, in which the first transducer means is a magnetostrictive transducer adapted to be mounted to the elongate member to produce longitudinal sonic vibrations in it.

12. Apparatus according to claim 10, in which the data parameter converting means is a fluid pressure transducer for monitoring fluid pressure below said obstruction.

13. Apparatus according to any of claims 9 to 12, in which said second transducer means comprises a mechanical bandpass filter and a piezoactive element mounted in series on the elongate member.

14. Apparatus according to any of claims 9 to 13, in which the signal processing means includes electronic filter means.

15. Apparatus according to any of claims 9 to 14, in which the signal processing means includes a memory for storing received data, and means for transferring data from the memory to a pick-up tool lowered to an adjacent location in the borehole.

16. Apparatus according to claim 15, in which the pick-up tool includes a further memory in which the data may be stored until the pick-up tool is returned to the surface.

17. Apparatus according to claim 15, in which the pick-up tool includes means for transmitting the data to the surface via a cable.

18. Apparatus according to any of claims 9 to 14 , in which the signal processing means includes a further electroacoustic transducer for retransmitting the data as an acoustic signal along the elongate member.



FIG. 1

SUBSTITUTE SHEET



FIG. 2



FIG. 3



Fig. 4

INTERNATIONAL SEARCH REPORT

International Application No PCT/GB 91/01599

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all)[6]

According to International Patent Classification (IPC) or to both National Classification and IPC

Int.Cl. 5 E21B47/12; G08C23/00

II. FIELDS SEARCHED

Minimum Documentation Searched[7]

Classification System	Classification Symbols
Int.Cl. 5	E21B ; G08C

Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched[8]

III. DOCUMENTS CONSIDERED TO BE RELEVANT[9]

Category °	Citation of Document, [11] with indication, where appropriate, of the relevant passages [12]	Relevant to Claim No.[13]
X Y	EP,A,0 033 192 (SPERRY CORPORATION) 5 August 1981 see page 1, line 1 - page 2, line 17; claims ---	1,2,6-14 3-4, 15-17
Y	GB,A,1 096 388 (TEXACO DEVELOPMENT CORPORATION) 29 December 1967 see the whole document ---	3,4, 15-17
X	US,A,4 293 936 (COX) 6 October 1981 see claims ---	1,2,5,6, 9,10,18
X	WO,A,8 910 573 (ATLANTIC RICHFIELD COMPANY) 2 November 1989 see page 2, line 16 - page 3, line 22; claims 1-4,12,13 ---	1,9

° Special categories of cited documents : [10]

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report
08 JANUARY 1992	17. 01. 92
International Searching Authority	**Signature of Authorized Officer**
EUROPEAN PATENT OFFICE	REEKMANS M. V.

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO. GB 9101599 SA 51504

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on 08/01/92
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
EP-A-0033192	05-08-81	US-A-	4283780	11-08-81
		US-A-	4302826	24-11-81
		US-A-	4282588	04-08-81
		JP-A-	56125595	01-10-81
GB-A-1096388		None		
US-A-4293936	06-10-81	CA-A-	1098202	24-03-81
		DE-A,C	2758770	20-07-78
		FR-A,B	2376288	28-07-78
		GB-A-	1598340	16-09-81
		JP-C-	1394519	11-08-87
		JP-A-	53101453	04-09-78
		JP-B-	62002113	17-01-87
WO-A-8910573	02-11-89	US-A-	4992997	12-02-91
		AU-A-	3689489	24-11-89

EPO FORM P0479

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82